



Data Sheet


Type Number 20319
Designation IEC SR527SW (SR64)
System Silver Oxide / Zinc /
 NaOH - Electrolyte

Nominal Voltage 1,55 V
Typical Capacity C 21 mAh
 Load 39 kOhm, at 20°C down to 1.2 V

Weight (approx.) 0,29 g
Volume 0,07 ccm
Coding..... Date of Manufacturing
 Month/Year



Temperature Ranges min max.
Storage 0°C 60°C
Discharge 0°C 60°C*

Dimensions min max.
Diameter (A) 5,65 5,80
Height (B) 2,50 2,70
Shoulder Diameter[E]..... 2,60
Shoulder Height [C]..... 0,08

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	1.2 V
Continuous 24h/d, 7d/w Current [μ A]:	39000 Ω	Time: Capacity [mAh]: Energy [mWh]:	560 h 21 32

* Contact VARTA if the application is intended to be outside the range of 0°C to +60°C.

Information and contents in this data sheet are for reference purpose only.
 They do not constitute any warranty or representation and are subject to change without notice.
 For most current information and further details, please contact your VARTA representative.

VARTA Microbattery GmbH, VARTA-Platz 1, D-73479 Eilwangen/Jagst
 Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-2553
 Date of issue: 2021-11-26

Subject to change without prior notice!