

# SEIZAIKEN

## QUALITY OF WATCH EXPERT



## SPECIFICATIONS

### Low Drain Battery

Model		Nominal Voltage (V)	Dimensions		Weight (g)	C.C.V. <sup>1*</sup>	
SEIZAIKEN			Diameter (mm)	Height (mm)		at 24°C (V)	at -10°C (V)
SR416SW	337	1.55	4.8	1.65	0.11	1.35	1.10
SR421SW	348	1.55	4.8	2.15	0.14	1.35	1.10
SR512SW	335	1.55	5.8	1.25	0.15	1.45	1.10
SR516SW	317	1.55	5.8	1.65	0.18	1.45	1.10
SR521SW	379	1.55	5.8	2.15	0.23	1.45	1.10
SR527SW	319	1.55	5.8	2.70	0.29	1.45	1.10
SR616SW	321	1.55	6.8	1.65	0.25	1.45	1.10
SR621SW	364	1.55	6.8	2.15	0.32	1.45	1.20
SR626SW	377	1.55	6.8	2.60	0.39	1.45	1.20
SR712SW	346	1.55	7.9	1.25	0.26	1.45	1.20
SR714SW	341	1.55	7.9	1.45	0.29	1.45	1.20
SR716SW	315	1.55	7.9	1.65	0.33	1.45	1.20
SR721SW	362	1.55	7.9	2.10	0.42	1.45	1.20
SR726SW	397	1.55	7.9	2.60	0.52	1.45	1.20
SR731SW	329	1.55	7.9	3.10	0.56	1.45	1.20
SR41SW	384	1.55	7.9	3.60	0.67	1.45	1.20
SR912SW	-	1.55	9.5	1.25	0.40	1.45	1.20
SR916SW	373	1.55	9.5	1.65	0.51	1.45	1.20
SR920SW	371	1.55	9.5	2.05	0.60	1.45	1.20
SR927SW	395	1.55	9.5	2.70	0.75	1.45	1.20
SR936SW	394	1.55	9.5	3.60	1.10	1.45	1.20
SR1120SW	381	1.55	11.6	2.05	0.93	1.45	1.20
SR1130SW	390	1.55	11.6	3.05	1.29	1.45	1.20
SR43SW	301	1.55	11.6	4.20	1.75	1.45	1.20
SR44SW	303	1.55	11.6	5.40	2.20	1.45	1.20

1\* C.C.V.: Closed Circuit Voltage / Low Drain 2kΩ 7.8msec Pulse

### High Drain Battery

Model		Nominal Voltage (V)	Dimensions		Weight (g)	C.C.V. <sup>2*</sup>	
SEIZAIKEN			Diameter (mm)	Height (mm)		at 24°C (V)	at -10°C (V)
SR626W	376	1.55	6.8	2.60	0.39	1.35	0.95
SR721W	361	1.55	7.9	2.10	0.41	1.35	1.05
SR726W	396	1.55	7.9	2.60	0.52	1.35	1.05
SR41W	392	1.55	7.9	3.60	0.67	1.35	1.05
SR920W	370	1.55	9.5	2.05	0.60	1.40	1.00
SR927W	399	1.55	9.5	2.70	0.75	1.40	1.05
SR1120W	391	1.55	11.6	2.05	0.93	1.40	1.20
SR1130W	389	1.55	11.6	3.05	1.29	1.40	1.20
SR43W	386	1.55	11.6	4.20	1.75	1.40	1.20
SR44W	357	1.55	11.6	5.40	2.20	1.40	1.20

2\* C.C.V.: Closed Circuit Voltage / High Drain 200Ω 5sec DC



Seiko Instruments Inc.  
[www.audisana.ch/shop](http://www.audisana.ch/shop)